

440 Vac 50 Hz

Πυκνωτές VRC 440 Vac 50 Hz

THDI_{MAX} <25% THDI_{ALARM} 50%

PF/R

ΣΕΙΡΑ	Τύπος Διαστάσεις	Ισχύς στα 400 Vac 50 Hz	Ισχύς βαθμίδων	Βήματα	Γενικός Διακόπτης	Ρυθμιστής Λέγγου Ισχύος	Όνομαστ. ένταση	Βάρος	Ισχύς στα 415 Vac 50 Hz
	Π x Β x Υ mm	kvar	kvar	Αρ.	A		A	kg	kvar
S 	PFS/R 460x215x450	13	1,875-3,75-7,5	7	45	PFC5	18	12	14
		18,5	3,75-7,5-7,5	5	45	PFC5	26	13	20
		26	3,75-7,5-15	7	63	PFC5	37	14	28
		30	7,5-7,5-15	4	63	PFC5	43	15	32
	PFS/R 610x215x450	35	1,875-3,75-7,5-15	19	100	PFC7	50	22	37,5
	PFS/R 460x215x450	37,5	7,5-15-15	5	100	PFC5	54	16	40
	PFS/R 610x215x450	45	7,5-7,5-15-15	6	100	PFC5	65	23	48
		52,5	7,5-15-15-15	7	125	PFC5	76	24	56,5
		60	7,5-7,5-15-15-15	8	160	PFC7	86	27	65
		67,5	7,5-4x15	9	160	PFC7	97	29	72,5
M 	PFM/R 420x380x700	75	7,5-15-22,5-30	10	250	PFC7	108	41	80
		105	7,5-15-22,5-30-30	14	250	PFC7	151	47	112
	PFM/R 420x380x920	127,5	7,5-15-22,5-30-52,5	17	400	PFC7	184	51	138
		150	15-30-45-60	10	400	PFC7	216	54	162
	PFM/R 420x380x1140	180	15-30-60-75	12	400	PFC7	259	60	194
		195	15-30-60-90	13	500	PFC7	281	65	210
225	15-30-60-120	15	500	PFC7	324	69	242		
I 	PIF/R 500x500x2000	240	30-30-60-60-60	8	630	PFC7	346	205	258
		300	30-30-60-60-120	10	800	PFC7	432	235	322
		360	30-60-60-90-120	12	800	PFC7	518	258	388
		420	30-60-90-120-120	14	1000	PFC7	605	271	452
L 	PFL/R 600x625x1315	300	30-30-4x60	10	800	PFC8	432	300	322
		375	37,5-37,5-4x75	10	1250	PFC8	540	340	404
	PFL/R 600x625x1565	450	45-45-4x90	10	1250	PFC8	648	360	484
		PFL/R 600x625x1815	525	52,5-52,5-4x105	10	1250	PFC8	756	400
L 	PFL/R 1200x625x1315	600	60-60-4x120	10	2x800	PFC8	864	560	646
		675	67,5-67,5-4x135	10	2x800	PFC8	972	640	726
	PFL/R 1200x625x1565	750	75-75-4x150	10	2x1250	PFC8	1080	660	807
		825	82,5-82,5-4x165	10	2x1250	PFC8	1188	700	888
		900	90-90-4x180	10	2x1250	PFC8	1296	720	968
	PFL/R 1200x625x1815	975	97,5-97,5-4x195	10	2x1250	PFC8	1404	760	1049
1050		105-105-4x210	10	2x1250	PFC8	1512	800	1130	